

METHOD OF DATA SYNCHRONIZATION

IN MULTIPLAYER NETWORK GAMES

5

The present invention relates to peer-to-peer on-line games and, more particularly, to a data synchronization method in multiplayer network games and a network game system using the same for the purpose of minimizing, through data synchronization, non-instantaneousness and non-reliability in data transmission due to physical limitations of networks.

BACKGROUND ART

15 With the propagation of the Internet, Internet users who enjoy on-line network games using the Internet have been explosively increased. These network games are executed in such a manner that a game server in which a manager site is open intermediates between user's terminals (referred to as "clients" hereinafter) On-line network games require synchronization that simultaneously displays variations in characteristics of objects used in the games on the terminal screens of games users in order that the users may enjoy the games in real time. However, networking includes 'non-reliability' and 'non-instantaneousness' so that data packets transmitted between clients on the Internet may be lost without warning notice and reception of the data packets within a limited time is not guaranteed. Furthermore, since 'reliability' and 'instantaneousness' are closely connected with each other, one of them becomes problematical when the other one is excessively pursued.

25

It is impossible to completely eliminate the aforementioned problem

because it is caused by physical limitations of networks. However, it is possible to hide the problem so as not to allow users to recognize it. For this, optimization techniques including dead reckoning technique using extrapolation and forward error correction technique is used.

5 However, these techniques should attach application logic to each of specific data fields loaded on data packets and separately process it. This makes the techniques sensitive to a variation in program versions and excessively increases complexity of program.

10

DISCLOSURE OF INVENTION

Accordingly, the present invention has been made in view of the aforementioned problems, and it is an object of the present invention to
15 provide a data synchronization method in multiplayer network games, comprising a first step of detecting data having a varied attribute from data constructing objects belonging to a first client according to logic of a game operated in the first client; and a second step of extracting varied contents of the detected data, segmenting the contents into packets, and transmitting the
20 packets to a second client, wherein the first and second steps are carried out by modules independent of each other.

In the present invention, the first step discriminates the data having a varied attribute from data constructing the objects. The second step transmits the packets using at least one of dead reckoning technique, forward error
25 correction technique, reliable transmission technique based on Negative Acknowledge ("NACK") and reliable transmission technique based on Acknowledge ("ACK") or a combination of these techniques. In addition, the

second step makes the first and second clients share information about their objects to synchronization data of the first client with data of the second client.

The present invention also provides a system for peer-to-peer ("P2P") network games, comprising a plurality of clients in which an application
5 program for a P2P network game is operated to execute the network game according to game logic; and a game server for mediating the network game among the clients, wherein the application program includes a game processing module that defines objects used in the game to execute the game and manages variations in attributes of the objects, and a communication
10 module that takes charge of communication between the game server and the clients and among the clients and, when there is a variation in the attributes of the objects, extracts varied contents to transmit them in unit of packets to the clients participating in the game.

In the present invention, each of the clients includes an object database
15 (DB) for storing data constructing the objects, and the communication module makes the clients participating in the game share their object DBs to synchronize data of the clients. The communication module transmits packets using at least one of dead reckoning technique, forward error correction technique, reliable transmission technique based on NACK and reliable
20 transmission technique based on ACK or a combination of these techniques.

BRIEF DESCRIPTION OF THE DRAWINGS

25

Further objects and advantages of the invention can be more fully understood from the following detailed description taken in conjunction with

the accompanying drawings, in which:

FIG. 1 is a schematic view showing the construction of a system for executing P2P network games according to the present invention; and

FIG. 2 is a schematic view showing the construction of a client
5 according to the present invention.

DETAILED DESCRIPTION OF THE INVENTION

10 The present invention will now be described in detail in connection with preferred embodiments with reference to the accompanying drawings.

FIG. 1 schematically shows the construction of a system for executing P2P network games according to the present invention.

A game server **100** manages information about clients **200** and **300**
15 participating in a game and their users and mediates P2P network games between the clients **200** and **300**. For example, the game server **100** memorizes IP address of the client **200** and then transmits it to the client **300** who wants to play a game with the client **200** so that a P2P network game having the client **200** as a server can be executed.

20 Upon the operation of a program for the P2P network game, the clients **200** and **300** play the P2P network game according to a game logic. To play the game, the clients **200** and **300** synchronize data in such a manner that they generate and delete objects (tanks, for example) used in the game, detect variations in data constructing the objects (for example, position, direction,
25 speed of a tank, direction of the gun barrel of the tank, firing time and direction, radio communication contents and so on) and transmit them to the counterpart clients **300** and **200**.

For data synchronization, the clients **200** and **300** transmit data packets through optimization techniques that include the dead reckoning method using extrapolative forecasting that forecasts the future based on the principle of continuity, forward error correction technique, reliable transmission technique based on NACK, and reliable transmission technique based on ACK. The forward error correction technique transmits additional information in addition to data information to allow a receiving side to detect an error existing in data using the additional information and to correct it. These optimization techniques are widely being used in wired and wireless communications so that detailed explanation therefor is omitted.

To use the optimization techniques, application logic should be given to each of data fields loaded on data packets and separately processed. For this, the present invention separately operates functions of conventional application for network games.

Specifically, in order to synchronize a variation in characteristic of an object (movement of a tank, for example) that is generated in a certain client **200** with the counterpart client **300**, the present invention separates a module (layer) that takes exclusive charge of communication-related operations, such as assembling and disassembling of data packets, transmission and retransmission of the data packets, and error data correction for informing the characteristic variation, from conventional application to separately operate the module.

The present applicant names the module that is exclusively responsible for the communication-related operations Nexus.

FIG. 2 schematically shows the construction of a client according to the present invention.

In the present invention, game application for executing a network

game is operated, being divided into two modules (layers), that is, game processing modules **220** and **320** and Nexuses **260** and **360** corresponding to communication modules. The game processing modules **220** and **320** operate a corresponding game program in the clients **200** and **300**, respectively. Nexuses
 5 260 and 360 transmit data about variations in objects.

The game processing modules **220** and **320** define the objects used in the game according to game logic and manage variations in attributes of the objects. That is, the game processing modules **220** and **320** generate and delete the objects and, if required, correct the attributes of the objects or read the
 10 attribute values of the objects.

Object DBs **240** and **340** store data required for the game processing modules **220** and **320** to operate the network game, respectively.

Nexuses **260** and **360** make the clients **200** and **300** participating in the game share data about their objects to synchronize variations in the data in real
 15 time. Specifically, when Nexus **260** senses a variation in data constructing an object of the object DB **240**, it detects which data item among the data constructing the object is varied and detects a degree of variation, disassembles the varied contents into packets, and then transmits the packets to the client **300**. The Nexus **360** at the receiving side assembles the received
 20 packets to update corresponding data of corresponding object belonging to the client **300** so as to synchronize the client **300** with the client **200**.

The receiving client displays the object constructed of varied data on the screen thereof.

The object DBs **240** and **340** store data constructing the objects used in
 25 the game. Each of the objects is constructed of attributes (parameters including the form, color, position, direction and size of an object) that define characteristics of the object. Each attribute value has time-dependency,

reliability level, time-constraint, and persistency.

A data synchronization method in a game played by the clients **200** and **300** is explained below.

5 A preparatory procedure for executing the game is identical to that of a conventional network game so that explanation therefore is omitted.

In the case that the user of the client **200** discharges a cannon ball from his/her tank (object) so that a variation in the attributes of the object (tank) occurs While clients **200** and **300**, remotely located, are playing a P2P network game, the game processing module **220** informs the object DB **240** of varied
10 data (attribute) among data items constructing the tank.

For example, the tank can discharge the cannon ball with the direction of its gun barrel changed while moving. Otherwise, the tank can fire the cannon ball by varying only the gun barrel without being moved. In the latter case, there is no need to transmit data about the position of the tank for
15 synchronization because the tank position is not changed.

Nexus **260** detects a degree of variation in corresponding data and transmits varied contents to Nexus **360** at the receiving side through a separate channel according to character of the data.

For example, Nexus **260** detects data about a moving distance and
20 moving direction of the gun barrel of the tank, a direction and rapidity of fire of the cannon ball, segments the data into packets, and sends the packets to Nexus **360**.

In prior arts, at this time, application logic is attached to each of data fields loaded on the data packets to separately process them in order to
25 transmit the varied contents of the object. However, the present invention can carry out this operation using Nexus **260** to transmit the packets using one of the above-described optimization techniques without complicating the game

operating program.

Nexus **360** at the receiving side assembles the packets received from Nexus **260** at the transmitting side to update the object DB **340** thereof.

That is, Nexuses **260** and **360** connect the object DBs **240** and **340**
5 under their management to each other to form a kind of common space so that the clients **200** and **300** can synchronize variations in their objects with each other.

The game processing module **320** displays data assembled by the Nexus **360** on the screen of the client **300**. Accordingly, the user of the client
10 **300** can see the varied object, that is, the object synchronized with the object displayed on the screen of the client **200**.

INDUSTRIAL APPLICABILITY

15

As described above, the present invention processes communication functions of transmitting and receiving a variation in objects, which were performed by application in prior arts, using a separate module. Accordingly, data synchronization in network games can be achieved without increasing
20 complexity of program.

While the present invention has been described with reference to the particular illustrative embodiments, it is not to be restricted by the embodiments but only by the appended claims. It is to be appreciated that those skilled in the art can change or modify the embodiments without
25 departing from the scope and spirit of the present invention.